

9. Declared performance:

The harmonised norm		EN16510-1:2022, EN16510-2-1:2022	
Maximum load chimney		120	kg
Chimney designation Tclass		T400G	
Safety distances	Front	1000	mm
	Rear	N/A	mm
	Side	900	mm
	Bottom	N/A	mm
	Ceiling	750	mm
	Floor radiation area	200	mm
	Side radiation area	900	mm
Protective isolation (insert)		mm	SILCA
Emissions		Nominal	Part-load
CO-emission (13% O ₂)		1220	mg/Nm ³
NOx-emission (13% O ₂)		111	mg/Nm ³
OGC-emission (13% O ₂)		61	mg/Nm ³
PM-emission (13% O ₂)		27	mg/Nm ³
Flue gas temperature		225	°C
minimum draught		12	Pa
Mass flow of flue gasses		7,3	g/s
Output		6	kW
Efficiency		78,6	%
Electrical consumption		0	0 kW
seasonal efficiency		68,6	%
Energy-efficiency-index		103,97	
Energy-efficiency-class		A	

10. The performance of the product described in points 1 and 2 conform with the performance reported in point 9.

This performance declaration is supplied under the exclusive responsibility of the producer specified in point 4:



25/09/2025 Weelde

Tom Gehem
CEO

Due to continuous product improvement, the supplied appliance specifications may vary from the description in this brochure without prior notice having been given.

DOVRE N.V.

Nijverheidsstraat 18 Tel : +32 (0) 14 65 91 91
B-2381 Weelde E-mail : info@dovre.be
Belgium