

9b. Declared performance SAGA 107:

The harmonised norm		EN16510-1:2022, EN16510-2-1:2022		
Maximum load chimney		120	kg	
Chimney designation Tclass		T400G		
Safety distances	Front	1000	mm	
	Rear	500	mm	
	Side	700	mm	
	Bottom	200	mm	
	Ceiling	750	mm	
	Floor radiation area	200	mm	
	Side radiation area	600	mm	
Protective isolation (insert)		-	mm	SILCA
Emissions		Nominal	Part-load	
CO-emission (13% O ₂)		904		mg/Nm ³
NOx-emission (13% O ₂)		128		mg/Nm ³
OGC-emission (13% O ₂)		35		mg/Nm ³
PM-emission (13% O ₂)		32		mg/Nm ³
Flue gas temperature		300		°C
minimum draught		12		Pa
Mass flow of flue gasses		8,5		g/s
Output		7,5		kW
Efficiency		75		%
Electrical consumption		0	0	kW
seasonal efficiency		65	%	
Energy-efficiency-index		98,75		
Energy-efficiency-class		A		

10b. The performance of the product described in points 1 and 2 conform with the performance reported in point 9.

This performance declaration is supplied under the exclusive responsibility of the producer specified in point 4:



25/09/2025 Weelde

Tom Gehem
CEO

Due to continuous product improvement, the supplied appliance specifications may vary from the description in this brochure without prior notice having been given.

DOVRE N.V.

Nijverheidsstraat 18 Tel : +32 (0) 14 65 91 91
B-2381 Weelde Email : info@dovre.be
Belgium